

# ***DYNAPAC TANDEM ASPHALT ROLLERS***



Dynapac CC800, CC900, CC900S, CC1000  
CC1100, CC1200, CC1300  
CC1100C, CC1200C, CC1300C

***Atlas Copco***





*DYNAPAC IS THE WORLD'S MOST SPECIALIZED* and experienced manufacturer of compaction and paving equipment. Our expertise has resulted in numerous successful innovations. To put it simply, we know this business and we've got the power to transform groundbreaking ideas into cost-efficient solutions and reliable machines.

## ***BUILDING ON EXPERIENCE***

That is why Dynapac is a winner when you compare overall profitability and life-cycle cost. In our lean and target-oriented organization there are very short and straight paths between development, manufacturing and our world-wide service network. Your benefit is quality all through - in products, maintenance, service and overall performance.

In this brochure we describe the basic characteristics of our small tandem vibratory rollers - a series of highly efficient rollers that can make your project more profitable and strengthen your reputation as a trustworthy working partner.

Welcome to the world of Atlas Copco Road Construction Equipment!







# SMALL SCALE COMPACTION WORK

**DYNAPAC'S RANGE OF SMALL TANDEM ASPHALT ROLLERS** – the Dynapac CC800, CC900, CC900S and CC1000 – are used primarily for small-scale compaction work such as pavements, cycle paths, small roads and small parking areas – places that need compaction but are difficult to reach with a larger roller.

These small tandem rollers come with an operating mass of approximately 1.6 tons and drum widths of 800, 900 and 1000 mm.

## GET THE JOB DONE

### LOW NOISE - HIGH POWER

The powerful and quiet water-cooled 3-cylinder Kubota diesel engine produces 18,1 kW (24.3 hp). With the large drum diameter and the drive motors connected in series, there is excellent accessibility and hill-climbing capability. Propulsion and vibration are standard on both drums.

As an option, vibration can be switched off on either the front or the rear drum.

### KEEPS GOING AND GOING

These rollers are equipped with an innovative sprinkler tube and nozzles that are self-draining to minimize the risk of ice plugs in cold weather.

The 110-litre water tank allows long periods of work between refills\*. To further extend the work periods, an optional sprinkler timer is available. The powerful water pump is the same model as used on our larger asphalt machines.

### OPERATOR FRIENDLY

A spacious, vibration-damped operator platform and an ergonomically positioned step make these machines extremely operator-friendly. A modern, easily legible instrument panel with a warning panel and a fuel gauge is standard.

### EASY TRANSPORTATION

To easily transport the roller between workplaces, the machines are fitted with a robust central lifting eye that allows fast and easy loading. An optional folding ROPS keeps the transport height to a minimum.

### MINIMUM SERVICE REQUIRED

Extended service intervals minimize maintenance costs. The machines have a maintenance-free steering hitch and steering cylinder. The few remaining service points are easily accessible.

*\* If you chose the PLUS-version, you will get an even larger watertank - 190 liters.*



### DYNAPAC CC900S

The "Single Arm" version - Dynapac CC900S - has the right side of the front drum free, which makes it possible to compact close to the walls. The front and rear drum have an offset of 60 mm.



## DYNAPAC CC800 CC900 CC900S CC1000

**”EXPERIENCE IS THE BASE OF EXCELLENCE. DYNAPAC WILL ALWAYS HELP YOU TO REACH PERFECTION.**

# ON TIME AND ON BUDGET

Powerful and silent 3 cylinder water cooled diesel engine.

Central lifting point.

Available with foldable ROPS.

Spacious operator platform.

Serial connected drum drive motors contribute to excellent hill-climbing capacity.

Fail-safe brakes

Ergonomic boarding steps.

Maintenance-free steering hitch and steering cylinder.

## GET THE JOB DONE. ON TIME AND ON BUDGET.



Easily readable instrument panel with fuel gauge.  
Very low vibration levels in the operator's platform.



Big drum diameter makes compaction easier even on soft tricky asphalt mixes. Thick drum shells for long life.



Pressurized sprinkler system with a powerful water pump and with self draining sprinkler tubes and nozzles.



Long service intervals together with maintenance free steering hitch and steering cylinder contribute to a minimum of maintenance.



A robust central lifting eye allows fast and easy loading.



A spacious vibration damped operator platform with comfort seat and dual forward/reverse levers for total operator comfort.



# CHOOSE BETWEEN CC AND CC PLUS PACKAGES



## CC PACKAGE FOR DYNAPAC CC800, CC900, CC900S AND CC1000

### INCLUDED:

Backup alarm  
Working lights

### OPTIONS FOR CC PACKAGE:

Foldable ROPS  
incl. seat belt, CE mark  
and rotating beacon



## CC PLUS PACKAGE FOR DYNAPAC CC800, CC900, CC900S AND CC1000

### INCLUDED:

Backup alarm  
CE sign  
Comfort seat  
Cup/can holder  
Foldable ROPS incl. seat belt  
Large Watertank, 190 l  
Rotating beacon  
Sprinkler timer  
Vibr. shut off, front or rear drum  
Working lights



### OPTIONS FOR CC PLUS PACKAGE:

Driving lights, right or left handed  
Dual forward/reverse control  
Rotating beacon, ignition controlled  
Spring loaded scrapers

## OPTIONS FOR CC AND CC PLUS DYNAPAC CC800, CC900, CC900S & CC1000

3" seatbelt  
Biodegradable hydraulic fluid  
Cert. fire protection, SBF 127  
Decal risk location (GOST)  
Fire extinguisher

Hearing protectors  
Licence plate light  
Rear view mirror, traffic view  
Service kit 50/500/1000 h  
Side direction lights (driving lights required)

Slow moving vehicle sign  
Special color (one or two)  
Tool set  
Water tank cover, lockable

# STREET-SMART COMPACT TANDEM ROLLERS

**DYNAPAC'S SERIES OF ARTICULATED COMPACT TANDEM ROLLERS** – the Dynapac CC1100, CC1200 and CC1300 – are designed for compaction on city streets where size and noise matter most. The series have an operating weight of 2,4 tons to 4 tons and are available with double steel vibratory drums or one vibration drum and four static rubber tires - a combi version. All models feature design improvements and an engine, which is quieter than ever.

## QUIETER THAN EVER

### ON THE SURFACE

All three double drum models feature vibration and drive on both drums. A large drum diameter makes them especially effective on soft asphalt. The ratio of drum diameter to static linear load reduces the risk of cracks.

All models in the series are perfect for urban areas, streets and roads. The CC1300 is also suitable for compacting subbases and bases and has the capacity to follow a small paver.

### IN THE DRIVER'S SEAT

An optional sideways sliding seat and operator-friendly dual front and reverse controls improve visibility for better control and better compaction. The ample clearance at the edge of the drums makes this true even close to high curbs.

The series feature a new control panel and low noise and vibration levels to reduce operator fatigue. A low center of gravity keeps the machines stable, and sturdy handgrips and steps enable safe boarding.

An interlock system prevents the engine from accidentally starting. An automatic brake lock is applied if the engine stops in the event of failure in the hydraulic or electric brake circuits.

### EASE OF MAINTENANCE

Three separate filters in the sprinkler water system ensure no clogged sprinkler nozzles. The entire system

can be drained easily without special tools. Filters for hydraulic fluid, engine oil and fuel are easily accessible.

Modularity is one of the corner-stones when it comes to building Dynapac rollers. These are built from a lot of existing parts. That means parts will be available in the future and that these models will be offered for several years to come – thus underscoring the high second-hand value of Dynapac equipment.

### SUSTAINABLE PRODUCTIVITY

Dynapac develops and manufactures products with the goal of sustainability: low operating costs and long-lasting quality equipment that creates high-quality results for the companies who use Dynapac. These articulated small tandem asphalt rollers are no exception.

The rollers are powered by a water-cooled Kubota diesel engine. The Dynapac CC1100 and CC1200 provide a power of 26 kW and the CC1300 provides 33 kW of power. The low noise level benefits the operator and the surroundings, especially during night work.

Long service intervals mean fewer oil changes and less money spent on routine maintenance. The corrosion-free water tanks are made of impact-resistant and recyclable polyethylene plastic. As an option, the machines can be equipped with bio-degradable hydraulic oil.



# DYNAPAC CC1100 CC1200 CC1300

## ALL MODELS AVAILABLE AS COMBI VERSION

The combi rollers reduce the risk of marring newly laid asphalt when making sharp turns.

The rubber tires are operated in pairs by separate drive motors.



Hydraulic fluid, engine oil and fuel system filters are easy to reach and easy to change. Long service intervals means less downtime.

The corrosion-free and impact-resistant water tank is made of recyclable material. Large opening for easy filling.

Silent water cooled diesel engine.

Safety interlock to prevent accidents – Operator must be in the seat before the engine will start.

Ergonomic F&R-handle

Automatic brake lock if the engine stops or if there is a failure in the hydraulic or electric brake circuits.

Easy-drained sprinkler system – no special tools required.



## ATTENTION TO DETAIL - THE BASE OF PERFECTION



Silent, powerful water cooled Kubota diesel engine. The large easy-to-open engine hood contributes to great accessibility.



The water tank has a large opening for easy filling.



3 sprinkler nozzles on all Dynapac CC1100-1300. 3 filters in the water system ensure clean water. Sprinkler timer is standard on Dynapac CC1300 as well as on all PLUS versions.



Fail safe brakes on both drums (or drum + combi wheels) which apply automatically in the event of failure in engine, hydraulics or electrical fault in the brake system.



Sturdy handgrips and ergonomic steps enable safe boarding.



High clearance of the edge of the drums facilitates compaction close to high curb stones. Excellent view over the drum edges for better control and compaction results.



# CHOOSE BETWEEN CC AND CC PLUS PACKAGES



## CC PACKAGE FOR CC1100, CC1200 & CC1300 + COMBI VERSIONS

### INCLUDED:

Backup alarm  
Working lights

### OPTIONS FOR CC PACKAGE:

Canopy roof without ROPS  
Foldable ROPS  
incl. seat belt, CE mark  
and rotating beacon



## CC PLUS PACKAGE FOR CC1100, CC1200 & CC1300 + COMBI VERSIONS



### INCLUDED:

Backup alarm  
Brake release  
CE Sign  
Dual arm rest  
Foldable ROPS incl. seatbelt  
Rotating beacon  
Sprinkler timer  
Slideable comfort seat  
Vibration shut off,  
front and reardrum  
Working lights

### OPTIONS FOR CC PLUS PACKAGE:

Driving lights, right and left handed  
Dual forward/reverse control  
Dual frequency (not for CE)  
Flow divider  
Slidable lux seat  
Spring loaded scrapers  
Rotating beacon, ignition controlled

## OPTIONS FOR CC & CC PLUS CC1100, CC1200 & CC1300 + COMBI VERSIONS

3" seatbelt

Biodegradable hydraulic fluid

Cert. Fire protection, SBF 127

Decal risk location (GOST)

Fire extinguisher

Foot rest

Hearing protectors

Licence plate light

Rear view mirror, traffic view

Service kit 50/500/1000H

Side direction lights (driving lights required)

Slow moving vehicle sign

Special color (one or two)

Tool set

Towing eyelet

Water tank cover, lockable

	CC800	CC900	CC900S	CC1000	CC1100	CC1200	CC1300
<b>DRUMS</b>							
Width, mm	800	900	900	1000	1070	1200	1300
<b>MASSES</b>							
Max. operating mass, kg	1,665	1,665	1,705	1,750	2,460	2,710	4,030
Operating mass (incl. ROPS), kg	1,575	1,600	1,660	1,685	2,350	2,600	3,900
Module mass (front/rear), kg	740 / 835	750 / 850	800 / 860	790 / 895	1,130 / 1,220	1,260 / 1,340	1,900 / 2,000
<b>TRACTION</b>							
Speed range	0-9	0-9	0-9	0-9	0-10	0-10	0-10
Vertical oscillation, °	±13	±13	±13	±13	±10	±10	±10
Theor. gradeability %	40 %	40 %	50 %	40 %	49 %	43 %	37 %
<b>COMPACTION</b>							
Centrifugal force, kN	17	17	17	17	28	32.5	33
Nominal amplitude, mm	0.4	0.4	0.35	0.33	0.5	0.5	0.5
Static linear load (front/rear), kg/cm	9.3/10.4	8.3 / 9.4	8.8 / 9.5	7.9 / 8.9	10.6 / 11.4	10.5 / 11.2	14.6 / 15.4
Vibration frequency, Hz	70	70	70	70	63	63	52
Water tank , l	110 CC 190 Plus	110 CC 190 Plus	110 CC 190 Plus	110 CC 190 Plus	160	160	200
<b>ENGINE</b>							
Manufacturer/ Model	Kubota D1105-E4B	Kubota D1105-E4B	Kubota D1105-E4B	Kubota D1105-E4B	Kubota D1703-M @2400	Kubota D1703-M @2400	Kubota V2203-M @2600
Rated power, SAE J1995 @2,800 rpm, kW/hp	18 / 24	18 / 24	18 / 24	18 / 24	26 / 35	26 / 35	33 / 44
Fuel tank capacity, l	23	23	23	23	50	50	50
	CC1100C	CC1200C	CC1300C	<b>HYDRAULIC SYSTEM</b>			
<b>DRUMS</b>				Driving Axial piston pump with variable displacement and servo.			
Width, mm	1070	1200	1300	2 radial piston motors with constant displacement.			
<b>Masses</b>				Vibration Gear pump/ motors with constant displacement.			
Max. operating mass, kg	2,440	2,570	3,900	Steering Gear pump with constant displacement.			
Operating mass (incl. ROPS), kg	2,300	2,430	3,750	Service brake Hydrostatic in forward and reverse lever.			
Module mass (front/rear), kg	1,130 / 1,170	1,260 / 1,170	1,930 / 1,820	Parking/ Emergency brake Failsafe brake in both drums.			
<b>TRACTION</b>							
Speed range	0-9,5	0-9,5	0-10				
Vertical oscillation, °	±10	±10	±10				
Theor. gradeability %	68 %	63 %	37 %				
<b>COMPACTION</b>							
Centrifugal force, kN	28	32.5	33				
Nominal amplitude, mm	0.5	0.5	0.5				
Static linear load (front/rear), kg/cm	10.6/ 11.3	10.5 / 11.2	14.8 / 14				
Vibration frequency, Hz	63	63	52				
Water tank , l	160	160	200				
<b>ENGINE</b>							
Manufacturer/ Model	Kubota D1703-M	Kubota D1703-M	Kubota V2203-M				
Rated power, SAE J1995 @2,800 rpm, kW/hp	@2400 26 / 35	@2400 26 / 35	@2600 33 / 44				
Fuel tank capacity, l	50	50	50				

## COMMITTED TO SUSTAINABLE PRODUCTIVITY

We stand by our responsibilities towards our customers, towards the environment and the people around us. We make performance stand the test of time.

This is what we call - Sustainable Productivity.

### Dynapac Compaction Equipment AB

Industrivägen 2, 371 31 Karlskrona, Sweden

Phone: +46 455 30 60 00 - Fax: +46 455 30 60 30 [www.atlascopco.com](http://www.atlascopco.com)

**Atlas Copco**